

SRM®200

Pocket size surface resistance meter with LCD display.

Includes conductive carrying case, grounding cord, USB-Cable, calibration certificate and software for reading the saved test data.



- Test range: $10^3 - 10^{12}$ ohm
- Test voltage: open circuit voltage 100 V (switches automatically above > 1 MOhm)
- Operation: Battery operated
- Display: LCD-Display
- Probes: Built-in electrodes with conductive rubber
- with memory and USB connection to PC
- 2 external probes connection possible



Built-in bar electrodes

Part Nr.

7100.SRM200.K Surface Resistance Meter SRM® 200

SRM®200/EFM®51 STARTERKIT

Starterkit for testing conductive an dissipative surfaces and electrostatic fields/surface potentials

Includes

- SRM®200 as described above
- EFM®51 (see page 79)
- conductive carrying case



Part Nr.

7100.SRM200.SK51 SRM®200/EFM®51 Starterkit

SRM®110

Pocket size, lightweight, **surface resistance meter**, includes carrying bag, grounding cord and calibration certificate.

- Test range: $10^3 - 10^{12}$ ohm
- Test voltage: open circuit voltage
- Operation: Battery operated
- Display: 12 LED display
- Probes: Built-in metal electrodes (2 external probes connection possible)



Built-in bar electrodes

Part Nr.

7100.SRM110.A Surface resistance meter SRM® 110

