

METRISO® 2000 TEST KIT

Metriso® 2000 - test kit includes: digital high resistance tester, temperature and relative humidity adapter, USB infrared adapter, PC software for Windows®, 2 probes, hand-held probe with connecting cables, user's instructions in German, English and French, calibration certificate, conductive carrying case fitted with dissipative pink foam.

- Suitable for resistance point-to-point and resistance to ground measurements
- Integrated data logger with infrared communication port for data transmission (2.500 test values)
- Clip-on humidity and temperature sensor

Test voltage: DC 10 volts, 100 volts, 250 volts and 500 volts
 Test range: 10^3 to 10^{12} ohm
 Operation: Battery operated
 Probes: 2 x Model 850 (weight: 2,27 kg / \varnothing 63,5 mm) with conductive rubber
 1 x hand-held probe Model 45

clip-on humidity and temperature sensor



Product link




complies with
 IEC 61340-4-1
 IEC 61340-2-3
 IEC 61340-4-5

Part Nr.


7100.2000.MK	Metriso® 2000 Test Kit, German version
7100.2000.MK.E	Metriso® 2000 Test Kit, English version
7100.2000.G	Metriso® 2000 Test Instrument only, German version
7100.2000.G.E	Metriso® 2000 Test Instrument only, English version

Accessories

7100.2000.TR50	50 m extension cable for floor measurements
7100.2000.ML	Replacement set of connecting cables (com/shield, +pole)



R_g system
 Resistance of person/
 ESD shoes/flooring to ground



R_{p-p}
 Point to Point
 Resistance



R_g/R_{gp}
 Resistance to ground
 or groundable point

