

METRISO® 3000 MESS-KIT

Metriso® 3000 - test kit includes: digital high resistance tester, temperature and relative humidity sensor, USB port, PC software for Windows®, 2 probes, a hand-held probe with connecting cable, user's instructions in German, English and French, calibration certificate, conductive carrying case fitted with dissipative pink foam.

- Suitable for resistance point-to-point and resistance to ground measurements
- Integrated data logger with USB communication port for data transmission (50.000 test values). The supplied Report Generating Software ETC allows to generate a complete test report
- Humidity and temperature sensor
- A barcode scanner can be used in order to record test points before testing

- Test voltage / Test current: $1 \text{ mA} \leq I \leq 1,3 \text{ mA}$
- Test range:

High ohmic range:	DC 10 volts, 100 volts and 500 volts
low ohmic range:	0 to 10 kOhm
High ohmic range:	1 kOhm to 1,2 TOhm
- Operation: Battery operated
- Probes:

2 x Model 850 (weight:	2,27 kg / ø 63,5 mm)
with conductive rubber	
1 x hand-held probe Model 45	

complies with
IEC 61340-4-1
IEC 61340-2-3
IEC 61340-4-5



Product link



T/H sensor

Interface for
T/H sensor and
barcode scanner



sockets to check
10 MOhm reference
resistor



Barcode scanner

Part Nr.

7100.3000.MK	Metriso® 3000 Test Kit, menu language German/English
7100.3000.G	Metriso® 3000 Test Instrument only, menu language German/English

Accessories

7100.2000.TR50	50 m extension cable for floor measurements
7100.2000.ML	Replacement set of connecting cables (com/shield, +pole)
7100.3000.SC	Barcode scanner